

SPS



Primer

Good filling primer.

- Good filling
- Easy to sand
- The basis for a good end result
- White spirit / white spirit based
- Ideal for outside

Primer

DESCRIPTION

Finess Primer is a moisture-regulating primer based on white spirit. For use on wood, sheet materials, pre-treated metal and plaster. It penetrates deeply into the wood and is easy to sand.

RECOMMENDED SYSTEM

Substrate: The substrate must be clean, dry, dust- and grease-free. For good edge coverage, slightly round sharp corners. Untreated wood: Degrease, sand lightly and make dust free. Metal: Degrease, make rust and dust free. Treat with rust preventive paint, followed by an intermediate coat of Finess Primer.

TECHNICAL DATA

Gloss level at 60°: matt
Solids content in volume: 62%
Water Vapour Permeability: yes

DRY TIMES BY 20° C/RH 50%

Touch dry: After 2 hours
Dry to recoat: After 18 hours

PRACTICAL CONSUMPTION

Approx. 13 - 16 m²/litre per coat, depending on the object to be painted and the application method.

SURFACE PREPARATION

Substrate: The substrate must be clean, dry, dust- and grease-free. For good edge coverage, slightly round sharp corners. Untreated wood: Degrease, sand lightly and make dust free. Metal: Degrease, make rust and dust free. Treat with rust preventive paint, followed by an intermediate coat of Finess Primer.

DIRECTIONS FOR USE

Stir well before use. Apply 1 or 2 layers inside, 2 layers outside with a brush, paint roller or paint sprayer. Sand lightly between coats, remove dust and filler if necessary. Prime and sand filled surfaces

APPLICATION & THINNING: BRUSH

Ready to use

APPLICATION & THINNING: ROLLER

Ready to use

APPLICATION & THINNING: AIRLESS SPRAY

Ready to use

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Ready to use

Date issued: 29/06/2026

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu

