

SPS



Wood tar

Tar-free coating for wood above ground level.

- Weather-resistant protection
- Silk matt
- Moisture regulating UV-resistant
- Fast drying
- Silk matt

Wood tar

DESCRIPTION

Wood tar is a tar-free coating based on synthetic resin and, because of its good UV resistance, it is excellent for protecting and embellishing overhead objects such as sheds, posts, fencing and panelling. Wood tar can be applied over surfaces treated with bitumen and carbolineum.

DRY TIMES BY 20° C/RH 50%

Touch dry:	After 5 hours
Dry to recoat:	After 6 hours
Fully cured:	After 24 hours

SURFACE PREPARATION

Substrate must be dry and grease-free. Remove loose old coats on wood and sand with sandpaper.

DIRECTIONS FOR USE

Apply in thin layers with brush, buckshot or roller.

APPLICATION & THINNING: BRUSH

Ready to use, dilute with approx. 5% white spirit if necessary.

APPLICATION & THINNING: ROLLER

Ready to use, dilute with approx. 5% white spirit if necessary.

REMARKS

Do not apply in rain, fog and a temperature below 5°C.

Date issued: 29/06/2026

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu

