

SPS



Multiprimer

Multi-purpose primer.

Universal primer
Water-soluble, fast-drying
For indoor and outdoor use

WWW.SPSBV.COM

Multiprimer

DESCRIPTION

Finess Multiprimer is a universal multifunctional, fast drying, low-odour, waterborne primer. For use on wood, MDF, PVC and non-ferrous metals (such as zinc and aluminium). For indoor and outdoor use and overpaintable with all Finess white spirit and waterborne lacquers.

RECOMMENDED SYSTEM

Stir well before use. Apply in 1 or 2 layers with an acrylic brush, acrylic roller or paint sprayer. Thin the first coat with up to 3% water if necessary, do not thin the second coat. Lightly sand and dust down between coats. Due to fast drying, do not paint large areas at once and always work wet-on-wet.

TECHNICAL DATA

Solids content in volume: 54 m/m %
Water Vapour Permeability: Yes

DRY TIMES BY 20° C/RH 50%

Touch dry: 1
Dry to recoat: After approx. 6 hours

PRACTICAL CONSUMPTION

Approx. 12-14 m²/litre per coat, depending on the object to be painted and the application method.

DIRECTIONS FOR USE

Stir well before use. Apply in 1 or 2 layers with an acrylic brush, acrylic roller or paint sprayer. Thin the first coat with up to 3% water if necessary, do not thin the second coat. Lightly sand and dust down between coats. Due to fast drying, do not paint large areas at once and always work wet-on-wet.

APPLICATION & THINNING: BRUSH

Max. 3 % water

APPLICATION & THINNING: ROLLER

Max. 3 % water.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Date issued: 29/06/2026

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu

