

SPS



Floor paint

Wear-resistant, silk-matt paint.

- Wear-resistant protection, solvent-based
- Resistant to oil and petrol
- For indoor use

Floor paint

ОПИСАНИЕ

Finess floor paint is a hard-wearing, silk-matt paint for decorative protection of cement and concrete floors, among others. Resistant to fuel, oil, salt water and hot car tyres. Not suitable for asphalt floors. For indoor use.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

Stir well before use. Apply crosswise in 2 layers with a flat, wide brush/brush or short-haired paint roller. Thin the first layer with 5-10% white spirit. Do not dilute subsequent coats. Lightly sand and dust down between coats.

ПРЕПОРЪЧИТЕЛНА СИСТЕМА

Substrate: The substrate must be sound and free from moss, algae and salt deposits, dirt, grease, dust, etc. before painting. Remove and/or repair loose layers or joints. Always clean with Finess Concrete & Cement Cleaner * Tip: Moisture: To ensure that the floor is sufficiently dry, lay a piece of plastic sheeting of approx. 1 m² on the floor to be treated and cover the sides with tape. Leave this in place for 24 hours. If after this period there is condensation under the foil or the concrete has turned dark or wet, the floor cannot be painted yet. **Adherence:** To make sure the substrate adheres well, cut an 'X' in the existing paint layer with a hobby knife, down to the concrete. Stick a piece of sturdy tape over this. Now remove the tape in one movement. If more than 25% of the test surface comes off, the entire paint layer should be removed before painting the floor. **New concrete floors:** Should be at least 6 weeks old before they can be painted (for every cm. layer thickness at least 1 week drying time). **Rough untreated concrete floors:** Thoroughly clean with Finess Concrete & Cement cleaner. **Untreated smooth concrete floors:** Roughen and/or etch with water and 10% hydrochloric acid. Rinse thoroughly with clean water and allow to dry. Then clean with Finess Concrete & Cement Cleaner. **Porous and powdery substrates:** Thoroughly clean with Finess Concrete & Cement Cleaner. After drying, pre-treat with Finess Primer Concrete & Floor Paint. **Painted substrates:** Scrape off, dust and clean thoroughly with Finess Concrete & Cement Cleaner. After drying, pre-treat with Finess Concrete & Floor Paint Primer. **Treated floors in good condition:** First clean thoroughly with Finess Concrete & Cement Cleaner. Then roughen and remove dust. **Treated floors in poor condition:** Remove loose particles and level any unevenness. Allow to dry, then clean with Finess Concrete & Cement Cleaner, roughen and dust off, and pre-treat with Finess Primer Concrete & Floor Paint.

ТЕХНИЧЕСКИ ДАННИ

Гланцово ниво при 60°: 30 - 35%
Съдържание на сухо вещество (по обем): Ca. 1,2 g/ml

ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир: 2 hours
Готов за повторно нанасяне: Yes
group_dry_40_full_cure: After approx. 72 hours

КОНСУМАЦИЯ

Approx. 12 m²/litre per coat, depending on substrate and application method.

ПОДГОТОВКА НА ПОВЪРХНОСТТА

It should be load-bearing and be cleaned of moss, algae and salt deposits, dirt, grease, dust, etc. before painting. Remove and/or repair loose layers or joints. Always clean with Finess Concrete & Cement Cleaner.

Дата на издаване: 29/06/2026

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

