

# SPS



## Floor paint

# Wear-resistant, silk-matt paint.

- Wear-resistant protection, solvent-based
- Resistant to oil and petrol
- For indoor use

# Floor paint

## DESCRIPTION

Finess floor paint is a hard-wearing, silk-matt paint for decorative protection of cement and concrete floors, among others. Resistant to fuel, oil, salt water and hot car tyres. Not suitable for asphalt floors. For indoor use.

## RECOMMENDED USE

Stir well before use. Apply crosswise in 2 layers with a flat, wide brush/brush or short-haired paint roller. Thin the first layer with 5-10% white spirit. Do not dilute subsequent coats. Lightly sand and dust down between coats.

## RECOMMENDED SYSTEM

**Substrate:** The substrate must be sound and free from moss, algae and salt deposits, dirt, grease, dust, etc. before painting. Remove and/or repair loose layers or joints. Always clean with Finess Concrete & Cement Cleaner \* **Tip: Moisture:** To ensure that the floor is sufficiently dry, lay a piece of plastic sheeting of approx. 1 m<sup>2</sup> on the floor to be treated and cover the sides with tape. Leave this in place for 24 hours. If after this period there is condensation under the foil or the concrete has turned dark or wet, the floor cannot be painted yet. **Adherence:** To make sure the substrate adheres well, cut an 'X' in the existing paint layer with a hobby knife, down to the concrete. Stick a piece of sturdy tape over this. Now remove the tape in one movement. If more than 25% of the test surface comes off, the entire paint layer should be removed before painting the floor. **New concrete floors:** Should be at least 6 weeks old before they can be painted (for every cm. layer thickness at least 1 week drying time). **Rough untreated concrete floors:** Thoroughly clean with Finess Concrete & Cement cleaner. **Untreated smooth concrete floors:** Roughen and/or etch with water and 10% hydrochloric acid. Rinse thoroughly with clean water and allow to dry. Then clean with Finess Concrete & Cement Cleaner. **Porous and powdery substrates:** Thoroughly clean with Finess Concrete & Cement Cleaner. After drying, pre-treat with Finess Primer Concrete & Floor Paint. **Painted substrates:** Scrape off, dust and clean thoroughly with Finess Concrete & Cement Cleaner. After drying, pre-treat with Finess Concrete & Floor Paint Primer. **Treated floors in good condition:** First clean thoroughly with Finess Concrete & Cement Cleaner. Then roughen and remove dust. **Treated floors in poor condition:** Remove loose particles and level any unevenness. Allow to dry, then clean with Finess Concrete & Cement Cleaner, roughen and dust off, and pre-treat with Finess Primer Concrete & Floor Paint.

## TECHNICAL DATA

Gloss level at 60°: 30 - 35%  
Solids content in volume: Ca. 1,2 g/ml

## DRY TIMES BY 20° C/RH 50%

Touch dry: 2 hours  
Dry to recoat: Yes  
Fully cured: After approx. 72 hours

## PRACTICAL CONSUMPTION

Approx. 12 m<sup>2</sup>/litre per coat, depending on substrate and application method.

## SURFACE PREPARATION

It should be load-bearing and be cleaned of moss, algae and salt deposits, dirt, grease, dust, etc. before painting. Remove and/or repair loose layers or joints. Always clean with Finess Concrete & Cement Cleaner.

Date issued: 29/06/2026

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Europalaan 9  
5232 BC 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)