

SPS



Floor paint

Wear-resistant, silk-matt paint.

- Wear-resistant protection, solvent-based
- Resistant to oil and petrol
- For indoor use

Floor paint

OMSCHRIJVING

Finess floor paint is a hard-wearing, silk-matt paint for decorative protection of cement and concrete floors, among others. Resistant to fuel, oil, salt water and hot car tyres. Not suitable for asphalt floors. For indoor use.

AANBEVOLEN GEBRUIK

Stir well before use. Apply crosswise in 2 layers with a flat, wide brush/brush or short-haired paint roller. Thin the first layer with 5-10% white spirit. Do not dilute subsequent coats. Lightly sand and dust down between coats.

AANBEVOLEN SYSTEEM

Substrate: The substrate must be sound and free from moss, algae and salt deposits, dirt, grease, dust, etc. before painting. Remove and/or repair loose layers or joints. Always clean with Finess Concrete & Cement Cleaner * **Tip: Moisture:** To ensure that the floor is sufficiently dry, lay a piece of plastic sheeting of approx. 1 m² on the floor to be treated and cover the sides with tape. Leave this in place for 24 hours. If after this period there is condensation under the foil or the concrete has turned dark or wet, the floor cannot be painted yet. **Adherence:** To make sure the substrate adheres well, cut an 'X' in the existing paint layer with a hobby knife, down to the concrete. Stick a piece of sturdy tape over this. Now remove the tape in one movement. If more than 25% of the test surface comes off, the entire paint layer should be removed before painting the floor. **New concrete floors:** Should be at least 6 weeks old before they can be painted (for every cm. layer thickness at least 1 week drying time). **Rough untreated concrete floors:** Thoroughly clean with Finess Concrete & Cement cleaner. **Untreated smooth concrete floors:** Roughen and/or etch with water and 10% hydrochloric acid. Rinse thoroughly with clean water and allow to dry. Then clean with Finess Concrete & Cement Cleaner. **Porous and powdery substrates:** Thoroughly clean with Finess Concrete & Cement Cleaner. After drying, pre-treat with Finess Primer Concrete & Floor Paint. **Painted substrates:** Scrape off, dust and clean thoroughly with Finess Concrete & Cement Cleaner. After drying, pre-treat with Finess Concrete & Floor Paint Primer. **Treated floors in good condition:** First clean thoroughly with Finess Concrete & Cement Cleaner. Then roughen and remove dust. **Treated floors in poor condition:** Remove loose particles and level any unevenness. Allow to dry, then clean with Finess Concrete & Cement Cleaner, roughen and dust off, and pre-treat with Finess Primer Concrete & Floor Paint.

TECHNISCHE GEGEVENS

Glansgraad bij 60°: 30 - 35%
Vaste stof gehalte in volume: Ca. 1,2 g/ml

DROOGTIJDEN BIJ 20° C/RV 50%

Kleefvrij: 2 hours
Overschilderbaar: Yes
Volledig uitgehard: After approx. 72 hours

PRAKTISCH VERBRUIK

Approx. 12 m²/litre per coat, depending on substrate and application method.

ONDERGROND VOORBEHANDELING

It should be load-bearing and be cleaned of moss, algae and salt deposits, dirt, grease, dust, etc. before painting. Remove and/or repair loose layers or joints. Always clean with Finess Concrete & Cement Cleaner.

Uitgiftedatum: 29/06/2026

Beschikbare kleuren en verpakkingsformaten: Raadpleeg de betreffende productpagina op www.rust-oleum.eu voor een overzicht van de actueel beschikbare kleuren en verpakkingsgrootten.

Disclaimer: De informatie in dit document is naar ons beste weten juist en wordt te goeder trouw, maar zonder garantie gegeven. De gebruiker wordt geacht onafhankelijk de geschiktheid van onze producten voor zijn/haar eigen specifieke toepassing te testen. In geen geval is Rust-Oleum Europe aansprakelijk voor directe of indirecte schade. Producten dienen te worden opgeslagen, behandeld en aangebracht volgens de aanbevelingen van Rust-Oleum Europe op het productinformatieblad (technische fiche). Het is de verantwoordelijkheid van de gebruiker om altijd de laatste versie van het productinformatieblad (technische fiche) te raadplegen en te respecteren. Deze bladen zijn gratis te downloaden van de website www.rust-oleum.eu of op aanvraag bij de afdeling Customer Service (Verkoop binnendienst). Rust-Oleum Europe houdt zich het recht voor om de eigenschappen van haar producten te wijzigen zonder voorafgaande kennisgeving.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

