



# SPS



## FAÇADE SATIN

### Satin, 100% acrylic facade paint

- Optimal flow
- Scrub-resistant
- class 1 (DIN EN 13300)
- 100% acrylate
- Excellent coverage

# FACADE SATIN

## ОПИСАНИЕ

Very high-quality, excellent covering, silk gloss, 100% acrylic wall paint. Excellent weather-resistant and scrub-resistant. Extremely suitable for durable finishing of exterior and interior walls. Can also be used in wet areas. For interior and exterior use.

## ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

For a durable finish on exterior facades and interior walls, also suitable for damp rooms. Perfect for interior and exterior paintwork with high demands. Suitable substrates include: existing wall paint layers, cement and plaster, concrete, brick, etc.

## ПРЕПОРЪЧИТЕЛНА СИСТЕМА

**New, untreated substrates** - Prime highly absorbent substrates completely with SPS Fix-Primer. - Clean powdery substrates thoroughly. Pre-treat with SPS Fix-Primer after drying. - Paint over **existing intact wall paint layers** - Clean. - If necessary, apply an intermediate coat of SPS Wall-Primer. - Paint off opaquely after drying. **Existing non-bearing wall paint layers** - Remove loose particles. - Wash off powdery layers thoroughly and allow to dry. - Carry out any necessary repairs. - Pre-treat with SPS Fix-Primer. - After drying, paint over the surface. **Contamination by nicotine, moisture, rust or soot** - Clean thoroughly. - Treat the surface/pollution with SPS Iso-Primer. - After drying, paint over the surface. The systems mentioned are general descriptions for most common substrates. For specific applications and/or detailed advice, please contact SPS bv.

## ТЕХНИЧЕСКИ ДАННИ

Плътност (г/см³):	1,30
Гланцово ниво:	sps_zijdeglans
Гланцово ниво при 60°:	40, satin
Съдържание на сухо вещество (по обем):	44%

## ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир:	2 hours.
Готов за повторно нанасяне:	4 - 6 hours.

## МОКЪР СЛОЙ

Approx. 111 micrometres.

## СУХ СЛОЙ

Approx. 48 micrometres.

## РАЗХОДНА НОРМА

Approx. 9 m² / litre per coat. The stated yield is theoretical.

## КОНСУМАЦИЯ

Actual consumption depends on the nature and structure of the substrate and the processing method.

## ПОДГОТОВКА НА ПОВЪРХНОСТТА

The substrate must be load-bearing, fully bonded, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers. For exterior use, remove all algae and moss deposits.

## НАЧИН НА УПОТРЕБА

Stir well before use. If necessary, dilute the first coat with up to 10% water. Apply with a suitable brush, roller or sprayer. Always work wet-on-wet to avoid swelling. Re-roll all surfaces in the same direction. Do not touch up while drying.

## УСЛОВИЯ ЗА НАНАСЯНЕ

Do not apply at temperatures below +8°C. Only apply when substrate temperature is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost, or in full sunlight.

## НАНАСЯНЕ И РАЗРЕЖДАНЕ: ЧЕТКА

Maximum 10% water.

## НАНАСЯНЕ И РАЗРЕЖДАНЕ: ВАЛЯК

Maximum 10% water.

## БЕЗВЪЗДУШНО ПРЪСКАНЕ (AIRLESS SPRAY)

Airless: Nozzle opening: 0.017-0.019", Pressure: approx. 180 bar, Dilute: Maximum 10% water.

Airmix: Nozzle opening: 0.017-0.019", Pressure: >120 bar, Air pressure: approx. 2 bar, Dilute: Maximum 10% water.

The specified settings for spraying this product are a starting point. Depending on site conditions, settings will have to be determined by the applicator.

## ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ

Water and soap.

## ЗАБЕЛЕЖКИ

The values listed in this technical data sheet are determined on the basis of DIN EN 13300. Always use the necessary personal protective equipment when handling this product. Do not inhale product vapour and spray mist. Always ventilate appropriately during processing. Dispose of residues of this material and its packaging to hazardous or special waste collection point.

## СРОК НА ГОДНОСТ

Minimum 12 months in well-sealed original container in dry, cool, and frost-free place.

Дата на издаване: 13/04/2026

**Налични цветове и размери на опаковките:** Моля, вижте съответната продуктова страница на [www.rust-oleum.eu](http://www.rust-oleum.eu), за да се запознаете с актуалните налични цветове и размери на опаковките.

**Отказ от отговорност:** Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от [www.rust-oleum.eu](http://www.rust-oleum.eu) или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

**Rust-Oleum Netherlands B.V.**  
Europalaan 9  
5232 BC 's-Hertogenbosch  
The Netherlands  
T: +31 (0) 165 593 636  
F: +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T: +44 (0)1914 113 146  
F: +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T: +33(0) 130 40 00 44  
F: +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T: +32 (0) 13 460 200  
F: +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

