



SPS



RENOCRYL ROOF

Roof renovation paint based on 100% acrylate

- Colourfast and UV-resistant
- Permanently elastic
- Breathable
- Easy to apply
- Excellent adhesion

RENOCRYL ROOF

ОПИСАНИЕ

Light silk-gloss, high-quality roof renovation paint based on 100% acrylate. The product makes old pitched roofs look like new again and extends their lifespan. Excellent adhesion and easy to apply. Provides long-term protection for concrete tiles, fibre cement slates or corrugated sheet against harmful weather influences, moss, mould, algae growth and acid rain. For exterior use.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

Outdoor application on weathered sloping roofs. Gives long-term protection to cement tiles, fibre cement slates or corrugated sheets against weathering, moss, mould, algae growth and acid rain.

ПРЕПОРЪЧИТЕЛНА СИСТЕМА

Check substrate for defects and/or leaks. Remove all loose parts with a wire brush or by scraping off with a putty knife. Then thoroughly clean with pressure washer or mechanically, so that all dirt, salt deposits, grease, dust, algae and moss are removed. Then rinse well with clean water and allow to dry. Avoid too long a period between cleaning and application of Renocryl Roof (max. 3 weeks). If the surface is highly absorbent and/or powdery, apply SPS Fix-Primer. The above is a general description. For specific applications and/or detailed advice, please contact SPS bv.

ТЕХНИЧЕСКИ ДАННИ

Плътност (г/см ³):	1,25
Гланцово ниво:	sps_zijdeglans
Гланцово ниво при 60°:	satin.
Съдържание на сухо вещество (по обем):	38%

ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир:	2 hours.
Готов за повторно нанасяне:	6 - 12 hours.

МОКЪР СЛОЙ

170 - 210 micrometres.

СУХ СЛОЙ

65 - 80 micrometres.

РАЗХОДНА НОРМА

2 - 2.5 m²/l/coat.

КОНСУМАЦИЯ

Actual consumption depends on the nature and structure of the substrate and the processing method.

ПОДГОТОВКА НА ПОВЪРХНОСТТА

The substrate must be load-bearing, completely sealed, clean, dry, dust- and grease-free. Repair cracks and fissures. Remove and/or repair loose and unstable layers. For exterior use, remove all algae and moss growth.

НАЧИН НА УПОТРЕБА

Stir well before use. Always apply in 2 layers with a brush, roller or airless sprayer. Dilute the first layer with 10% water, depending on the absorbency of the substrate. Airless spray: dilute the first coat approx. 10% with water. After approx. 1 hour drying (depending on outdoor temperature) of the first coat, apply the second coat undiluted. Always work wet-on-wet when spraying.

УСЛОВИЯ ЗА НАНАСЯНЕ

Do not apply at temperatures below +8°C. Only apply when the temperature of the substrate is at least 3°C above the dew point temperature. Do not apply outdoors under threat of rain, frost, or in full sunlight.

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ЧЕТКА

Maximum 10% water (first layer).

НАНАСЯНЕ И РАЗРЕЖДАНЕ: ВАЛЯК

Maximum 10% water (first layer).

БЕЗВЪЗДУШНО ПРЪСКАНЕ (AIRLESS SPRAY)

Airless: Nozzle opening: 0.017-0.023", Pressure approx. 150 bar, Dilute max. 10% (1st layer)

The specified settings for spraying this product apply as a starting point. Depending on site conditions, settings will have to be determined by the applicator.

ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ

Water and soap.

ЗАБЕЛЕЖКИ

The values listed in this technical data sheet are determined on the basis of DIN EN 13300. Always use the necessary personal protective equipment when handling this product. Do not inhale product vapour and spray mist. Always ventilate appropriately during application. Dispose of residues of this material and its packaging to hazardous or special waste collection point.

СРОК НА ГОДНОСТ

Minimum 12 months in tightly closed original container in dry, cool, frost-free place.

Дата на издаване: 26/06/2026

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu

