

SPS



SATIN PU-A

Satin-gloss PU acrylic paint

- Resistant to oils from the skin
- Good retention of colour and gloss
- Perfect flow
- Scratch-resistant
- Virtually odourless and quick drying

SATIN PU-A

ОПИСАНИЕ

Water-based, durable, scratch-resistant and satin-gloss PU acrylic paint with good retention of colour and gloss. For a decorative finish on wood, hard plastics and metal. Resistant to skin oils, quick drying, odourless and low in solvents. For interior use.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

As a top coat paint on pre-treated wood substrates. In addition, as a top coat paint on pre-treated plastic or metal substrates.

ПРЕПОРЪЧИТЕЛНА СИСТЕМА

General: The surface must be capable of supporting the paint, clean, dry and free of dust or grease. Slightly round off sharp edges to obtain good edge coverage.

Exposed/untreated wood

- Prime untreated wood with SPS Multiprimer and types of wood that bleed with SPS Primer ISO.

- Allow to dry, lightly sand and remove dust.

- Apply top coat paint.

Existing old coats

- Remove old loose coats.

- Clean the entire surface using SPS Paint cleaner.

- Sand decayed wood down to healthy wood before applying primer.

- Carry out any repairs and apply primer.

- Allow to dry, sand and remove dust.

- Prime exposed areas with SPS Multiprimer or, in the case of types of woods that bleed, with SPS Primer ISO.

- Allow to dry, lightly sand and remove dust.

- Apply top coat paint.

Existing intact coats of paint

- Clean the intact coats using SPS Paint cleaner

- Sand the surface well.

- Touch up with primer or apply a complete coat of primer using SPS Multiprimer.

- Allow to dry, lightly sand and remove dust.

- Apply top coat paint.

ТЕХНИЧЕСКИ ДАННИ

Плътност (г/см³): 1.20

Гланцово ниво: sps_zijdeglans

Съдържание на сухо

вещество (по обем): 35%

ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

Сух на допир: 1 hour

Готов за повторно

нанасяне: 6 hours

МОКЪР СЛОЙ

67 µm

СУХ СЛОЙ

23 µm

РАЗХОДНА НОРМА

14 - 16m²/litre per coat

КОНСУМАЦИЯ

The actual coverage depends on the nature and the structure of the surface and the application method.

НАЧИН НА УПОТРЕБА

Stir thoroughly prior to use. Apply in 1 or 2 coats using a suitable brush or paint roller.

Water-based products dry relatively quickly. Always work wet-on-wet to prevent marks in the paint. Do not touch up when drying.

УСЛОВИЯ ЗА НАНАСЯНЕ

Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

Products based on alkyd resins tend to yellow in a dark environment or when covered. In an environment where they are exposed to daylight, this tendency to yellow is much reduced. This SPS product is resistant to skin oils. The degree of resistance to skin oils of the paint coats depends on the type of surface contamination and exposure time. Regular cleaning using a suitable cleaning agent extends the life of the paint coat.

ДАНИ ЗА БЕЗОПАСНОСТ

Ниво на ЛОС: 40 g/l

Категория ЛОС: A/d

group_voc_40_limit: 130 g/l

Забележки относно безопасността: This product and the packaging should be disposed of at a collection point for hazardous or special waste.

PH

9

СРОК НА ГОДНОСТ

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Дата на издаване: 28/11/2025

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu



WWW.SPSBV.COM