

# SPS



## TRANSPARANT UV

### High-gloss transparent top coat based on an alkyd resin

- Protects against UV radiation
- Moisture regulating
- Accentuates the wood grain
- High coating thickness
- Excellent weather resistance

# TRANSPARENT UV

## ОПИСАНИЕ

Extra durable, moisture regulating and high-gloss transparent top coat paint for exterior use, based on an alkyd resin. High coating thickness and UV filter for long-lasting protection from wood. Accentuates the grain. For exterior use.

## ПРЕПОРЪЧИТЕЛНА УПОТРЕБА

Due to the special UV filter, suitable as a transparent primer, pre-coat and top coat on wooden substrates. Despite containing a UV filter, colourless SPS Lacquer Transparent UV is more sensitive to weather than coloured Lacquer Transparent because it does not contain any pigments.

## ПРЕПОРЪЧИТЕЛНА СИСТЕМА

**General:** The surface must be capable of supporting the paint, clean, dry and free of dust or grease. Slightly round off sharp edges to obtain good edge coverage. Always sand in the direction of the grain.

### Exposed/untreated wood

- Clean the entire surface using SPS Paint cleaner.
- Sand lightly in the direction of the grain and wipe off any dust residue.

### Existing old coats

- Thoroughly remove loose coats.
- Clean the complete surface with SPS Paint cleaner, sand in the direction of the grain and remove any sanding dust.
- Sand decayed wood down in the direction of the grain until you reach healthy wood.

### Existing intact coats of paint

- Clean the intact coats of paint with SPS Paint cleaner, sand in the direction of the grain and remove any sanding dust.
- Sand decayed wood down in the direction of the grain until you reach healthy wood.

The systems described above apply for the most common types of surface. For specific applications and/or detailed advice, please contact SPS bv.

## ТЕХНИЧЕСКИ ДАННИ

|                                        |               |
|----------------------------------------|---------------|
| Плътност (г/см³):                      | 0.95          |
| Гланцово ниво:                         | sps_hoogglans |
| Гланцово ниво при 60°:                 | 87-80%        |
| Съдържание на сухо вещество (по обем): | 52%           |

## ВРЕМЕ ЗА СУШЕНЕ ДО 20° C/RH 50%

|                             |          |
|-----------------------------|----------|
| Сух на допир:               | 4 hours  |
| Готов за повторно нанасяне: | 18 hours |

## МОКЪР СЛОЙ

63 µm

## СУХ СЛОЙ

33 µm

## РАЗХОДНА НОРМА

Approx. 14 - 16 m²/litre per coat

## КОНСУМАЦИЯ

The actual coverage depends on the nature and the structure of the surface and the application method.

## НАЧИН НА УПОТРЕБА

Stir thoroughly prior to use. Apply in 1 or more coats in the direction of the grain using a suitable (flat) brush. Always work wet-on-wet to prevent marks in the paint. Do not touch up when drying. Lightly sand in the direction of the grain in between coats and wipe off any dust residue before applying the next coat.

## УСЛОВИЯ ЗА НАНАСЯНЕ

Do not apply at temperatures below +8°C. Only apply if the surface temperature is at least 3°C above the dew point temperature. Do not apply outdoors when it is likely to rain, when frost is expected or in direct sunlight. Always use the required personal protective equipment when applying this product. Always ventilate appropriately when applying.

Products based on alkyd resins tend to yellow in a dark environment or when covered. In an environment where they are exposed to daylight, this tendency to yellow is much reduced.

## ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ

White spirit or cleaner

## ЗАБЕЛЕЖКИ

Variations in coating thickness, temperature, humidity, etc. affect the drying time.

## ДАНИИ ЗА БЕЗОПАСНОСТ

|                                  |                                                                                                            |
|----------------------------------|------------------------------------------------------------------------------------------------------------|
| Ниво на ЛОС:                     | 400 g/l                                                                                                    |
| Категория ЛОС:                   | A/e                                                                                                        |
| group_voc_40_limit:              | 400 g/l                                                                                                    |
| Забележки относно безопасността: | This product and the packaging should be disposed of at a collection point for hazardous or special waste. |

## СРОК НА ГОДНОСТ

Minimum of 12 months in the tightly sealed original packaging in a dry, cool and frost-free place.

Дата на издаване: 16/12/2025

**Налични цветове и размери на опаковките:** Моля, вижте съответната продуктова страница на [www.rust-oleum.eu](http://www.rust-oleum.eu), за да се запознаете с актуалните налични цветове и размери на опаковките.

**Отказ от отговорност:** Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от [www.rust-oleum.eu](http://www.rust-oleum.eu) или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)



[WWW.SPSBV.COM](http://WWW.SPSBV.COM)